AERODROME CHART - ICAO

ARP
43° 49' 28.1" N
018° 19' 54.4" E

AD ELEV 1705 ft

APP 136.450; 119.775
TWR 118.250

GND 121.900
ATIS 124.125

SARAJEVO / Sarajevo
BOSNIA AND HERZEGOVINA

DECLARED DISTANCES				
RWY	TORA	TODA	ASDA	LDA
11	2600	2600	2600	2500
29	2600	2600	2600	2100

INTERSECTION TAKE OFF				
RWY	INTERSECTION	TORA	TODA	ASDA
29	B	1730	1730	1730
11	C	1280	1280	1280
29	C	1140	1140	1140

TWY			
TWY	WIDTH	SFC	Bearing strength PCN
A	23 M	ASPH	PCN 60/F/C/X/T
B	18 M	ASPH	PCN 60/F/C/X/T
C	18 M	ASPH	PCN 60/F/C/X/T

RWY	LIGHTING 1)	
	APROACH	RUNWAY
11	HIRL	2)
29	-	-

APRON	
SFC	Bearing strength PCN
CONC	PCN 70/R/C/W/T 3)

RWY		
RWY	SFC	Bearing strength PCR
11	ASPH	PCR 740/F/D/X/T
29	ASPH	PCR 740/F/D/X/T

Aerodrome notes:

1) RWY LGT: edge lights: HIRL (1%, 3%, 10%, 30%, 100%) - omnidirectional,
centre line: HIRL (1%, 3%, 10%, 30%, 100%) - bidirectional.
Non/break backup power.

2) RWY 11: flashing lights system, taxiway and apron lights switch. (LOW, MEDIUM, HIGH)

3) STANDS 10, 10A, 11 and 11A ASPH PCN 60/F/C/X/T REF PARKING DOCKING CHART

Warning:

Bird concetration on and in the vicinity of RWY. Caution advised.

THR 11 Runway Turn Pad marking

RESTRICTION:
See AD 2.9.4



THR 29 Runway Turn Pad marking

RESTRICTION:
See AD 2.9.4



N
VAR 5° E (2020)

Annual Rate of Change 0.13° increasing

100 0 500 m

M 1:10 000

BEARINGS ARE MAGNETIC
ELEVATIONS IN FT
DISTANCES IN M

CHANGE: Separate Table for TWYs, APRON and RWYs; ADDED: Width for TWYs; Enlarged Layout of THR 11 and THR 29 Runway Turn Pad Marking.

THIS PAGE INTENTIONALLY LEFT BLANK