LQCG - CILJUGE

Note: The following sections in this chapter are intentionally left blank: AD-4.4, AD-4.5, AD-4.7, AD-4.8, AD-4.11, AD-4.13, AD-4.14, AD-4.15, AD-4.16, AD-4.19, AD-4.20, AD-4.21, AD-4.24, AD-4.25

LQCG AD 4.1 AERODROME LOCATION INDICATOR AND NAME

LQCG - CILJUGE

LQCG AD 4.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	442609.75N 0184111.67E
2	Direction and distance from (city)	3KM SE from Živinice
3	Elevation/Reference temperature	725 FT/23° C
4	Geoid undulation at AD ELEV PSN	NIL
5	MAG VAR/Annual Change	5° E (2020)/0.1° increasing
6	Name of airfield operator Address Telephone Telefax AFS SITA E-mail URL	Post: Aero klub "Fenix" Živinice Letilište Ciljuge bb 75270 Živinice Bosnia and Herzegovina Phone: +387 62 340 872 +387 61 151 380 +387 61 644 676 Fax: NIL AFS: NIL SITA: NIL E-mail: aeroklub.fenix@gmail.com URL: NIL
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	First landing of VFR flights to and departure from Bosnia and Herzegovina must be performed to/from one of International Airports (LQBK, LQMO, LQSA or LQTZ).

LQCG AD 4.3 OPERATIONAL HOURS

1	AD operator (AIRFIELD)	No specific working hours - (in accordance with activities of Aeroclub "Fenix" and/or O/R)
2	Customs and immigration	NIL
3	Health and sanitation	In Živinice, H24
4	AIS Briefing Office	Provided by: TUZLA ARO AFTN: LQTZZPZX PHONE: +387 35 745 530 FAX: +387 35 745 532 EMAIL: tuzla.aro@bhansa.gov.ba
5	ATS Reporting Office (ARO)	
6	MET Briefing Office	Provided by: TUZLA MET AFTN: LQTZYMYX PHONE: +387 35 745 746 FAX: +387 35 745 532 EMAIL: tuzla.met@bhansa.gov.ba
7	ATS	NIL
8	Fuelling	NIL
9	Handling	NIL
10	Security	NIL
11	De-icing	NIL
12	Remarks	AD approved for daylight operations only

LQCG AD 4.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 1
2	Rescue equipment	NIL
3	Capability for removal of disabled aircraft	NIL
4	Remarks	CAT 2 or CAT 3 on request 48 HR per notice

LQCG AD 4.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	NIL
2	RWY and TWY markings and LGT	RWY LDG: Direction indicator RWY EDGE: White Lines
3	Stop bars	NIL
4	Remarks	NIL

LQCG AD 4.10 AERODROME OBSTACLES

1. OBSTACLES IN AREA 2

Obstacle ID	Obstacle type	Coordinates	ELEV at TOP/ HGT	Marking / LGT type / colour	Remarks
1	2	3	4	5	6
NIL	Metal gate	442616.65N 0184053.60E	2.25 M AGL	Red and white	On the extended RWY axis, 95 M Northwest from THR 11. The gate can be opened (17 M wide)
NIL	Pole	442616.57N 0184050.21E	8 M AGL	NIL	165 M in direction 285 GEO from THR 11, and 36 M from extended RWY centre line (the bicycle track lighting pole)

2. OBSTACLES IN AREA 3

Obstacle ID	Obstacle type	Coordinates	ELEV at TOP/ HGT	Marking / LGT type / colour	Remarks
1	2	3	4	5	6
NIL	NIL	NIL	NIL	NIL	NIL

LQCG AD 4.12 RUNWAY PHYSICAL CHARACTERISTICS

RWY Designator	True BRG	Dimensions of RWY (M)	Strength (PCN) and surface of RWY and SWY	THR COORD, RWY end COORD, THR GUND	THR ELEV and highest ELEV of TDZ of precision APP RWY
1	2	3	4	5	6
11	118°	710 X 18	Strength: up to 5700 KG MTOW Surface:ASPH	442615.14N 0184057.49E NIL NIL	THR 731 FT TDZ NIL
29	298°	710 X 18	Strength: up to 5700 KG MTOW Surface:ASPH	442604.35N 0184125.85E NIL NIL	THR 719 FT TDZ NIL

Slope of RWY-SWY	SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)	OFZ	Remarks
7	8	9	10	11	12	13
- 0.60%	NIL	NIL	NIL	NIL	NIL	NIL
+ 0.60%	NIL	NIL	NIL	NIL	NIL	NIL

LQCG AD 4.17 ATS AIRSPACE

1	Designation and lateral limits	CILJUGE [1)] 442659N 0184104E; 442551N 0184502E; 442200N 0184650E; 442215N 0183703E; 442625N 0183653E; 442659N 0184104E.
2	Vertical limits	GND - 5500 FT AMSL
3	Airspace classification	D (during Tuzla ATS OPR HR) G (outside of Tuzla ATS OPR HR)
4	ATS unit call sign Language(s)	NIL Bosnian / English
5	Transition altitude	10000 FT AMSL
6	Hours of applicability	NIL
7	Remarks	[1)] Sport, glider and parachuting area LQCG is located inside of LQTZ CTR. Arriving aircraft shall contact Tuzla TWR prior to entering Tuzla CTR. Aircraft departing LQCG shall contact Tuzla TWR before departure from LQCG, while on the ground.

LQCG AD 4.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
INFO	CILJUGE	123.500 MHZ	O/R	NIL

LQCG AD 4.22 FLIGHT PROCEDURES

1. Both traffic patterns can be used (North and South). Traffic pattern altitude is 1000 FT AGL. Due to proximity to LQTZ, a pilot must request permission from Tuzla TWR before using the NORTH traffic pattern.

2. Due to obstacle West of THR 11, taking-off RWY 29 and landing RWY 11 are allowed with HEADWIND only (5 Knots or more). No restrictions for taking-off RWY 11 and landing RWY 29.

LQCG AD 4.23 ADDITIONAL INFORMATION

1. The use of the airfield without previous announcement to the airfield operator is prohibited.

2. During LQTZ ATS working hours all operations on LQCG must be approved by Tuzla TWR.

3. There is an asphalt bicycle track passing immediately by and parallel to the airstrip (all the way along the Southern border of the airstrip). There is no fence between the bicycle track and the airstrip and taxiway. Warning: There is a possibility of sudden appearance of people, animals or vehicles on the RWY and TWY.